AUTOPHIX BT500 Pro

OBDII+Battery Tester

Autophix BT500 Pro is a full-mode OBDII code reader with loading a high-configuration battery test 12V & 24V lead-acid batteries and lithium batteries it covers 4 major functions: Battery Test, Cranking Test, Charging Test and Review Data.

Diagnostic Advantages:

BATTERY TEST

Battery Type

- Regular Flooded
- AGM Flat plate
- AGM Spiral
- GEL
- EFB

CRANKING TEST

Support Battery

12V & 24V

CHARGING TEST

REVIEW DATA

OBDII Mode Functions

1.Read & clear codes

2.Display I/M readiness status

3.Read live data stream

4.View freeze frame data

5.Display live O2 sensor test data

6.On-board diagnostic monitoring tests

7.Evap system test

8.Retrieve vehicle information VIN,CIN and CVN)

I/M HOT KEY

Help Function ①

Quickly know the possible causes of error code, which saves time and money to repair!

Review

Record and playback DTCs what already appeared.

Relevant characteristics

Relevant characteristics of battery tests

1. Reverse connection protection with polarity. The battery and the instrument will not be damaged.

2. Over-voltage protection

If the positive and negative poles of the battery clips are not properly clipped, the following display will appear and the buzzer will be triggered.

Data print

Connect the device to the computer, print out records for both DTC data and Battery test data.

Multi Language Support

Multilingual menu options and code definitions.

Support 16 languages:

Japanese, English, French, Spanish, German, Russian, Italian, Portuguese, Polish, Hollandish, Finnish, Czech, Dutch, Norsk, Portuguese(Brazil).

It is shipped with multi-language menus, choose your language you want.

Product Dimensions

Comparing with other universal scanners, BT500 Pro has the 2.8 inch colour screen, you don't always need turn page when look up the menu or check diagnostic information, it is convenient for users.

Product Appearance

Product packaging

Super Durable

Safety and environmental protection: BT500 Pro adopts environmentally friendly materials and has passed CE, RoHS, FCC, REACH, PAHS, SOPS testing.

BSCI

Business Social Compliance Initiative

Conducts BSCI audit by TUV Rheinland.

Product Specifications

Display	2.8" LCD TFT 262K true color
Operating Temperature	0 to 50℃ (32℉ to 140℉)
Storage Temperature	-20 to 70℃ (-4℉ to 158℉)
External Power	8.0 to 30V power provided via vehicle battery
Dimensions	155.30mm*87.60mm*31.80mm